


DULUX ALL



Product Name	Dulux All
Product Code	A966-Line
Usage	Dulux All is a multifunctional all-in-one premium interior emulsion, for use on all interior wall surfaces. Specially formulated to provide superior toughness, anti-bacterial properties, outstanding washability and low odour. Dulux All is the complete multi-function solution. Dulux All conforms to the Singapore Green Labelling Scheme (032-038-0501).
Pack Size	1 and 5 litres
Colour Range	See appropriate Colour Card
Film Properties	
<i>Water Resistance</i>	Will tolerate the levels of atmospheric humidity present in normal interior environments and will withstand vigorous washing. Excellent scrubability and stain resistance. Extremely hardwearing and excellent adhesion.
Composition (nominal)	Pigment : Lightfast Non-lead Pigments Binder : Acrylic Emulsion Solvent : Water
Volume Solids	White 41%, other colours will vary
Drying Times	Single coat at standard thickness: <i>Touch Dry</i> : Dependent on temperature and humidity <i>Recoat</i> : 2 - 4 hours
Film Thickness	30 - 40 microns dry film thickness
Theoretical Coverage	Theoretical coverage which can be achieved under normal conditions is 13 m ² /litre on smooth surfaces of average porosity at 30 microns dry film thickness.
Application	
Thinning	
<i>Brush or Roller</i>	For normal use thinning is not usually necessary, but if required add up to 1 part of clean water to 10 parts of paint (10%).
<i>Conventional Spray</i>	Add up to 1 part of clean water to 10 parts of paint (10%).
<i>Airless Spray</i>	Add up to 1 part of clean water to 10 parts of paint (10%).

Spray Recommendations		
<i>Conventional Spray</i>	Satisfactory through most equipment.	
<i>Airless Spray</i>	A typical set up for airless spray application would be a minimum working pressure on paint of 140 kg/cm ² (2000 lb/sq in) with a spray tip size 0.38mm (15 thou) and a spray tip angle 65°.	
Cleaning Up		
Clean all equipment with clean water immediately after use.		
Surface Preparation		
Surface must be sound, clean, dry and free from all defective or poorly adhering material, dirt, grease or wax and be rubbed down using a suitable abrasive paper and dusted off. Treat areas affected by fungi or algae with Dulux Fungicidal Wash. If surfaces remain powdery or suffer from alkali attack after thorough preparation, seal with one coat of an appropriate sealer.		
System Information	Sealer (1 coat)	Finish (2 coats)
<i>Powdery and Alkaline Surfaces</i>	Dulux Sealer (solvent-based)	
<i>New Surfaces</i>	Dulux Sealer (water-based)	Dulux All
<i>Normal, Sound Surfaces</i>	No sealer required	
Health, Safety and Environment Information		
Product Safety Data Sheet available upon request.		

For further information or if you have any concerns about using this product, contact us at:

Akzo Nobel Paints (Singapore) Pte Ltd
 AkzoNobel House, 3 Changi Business Park Vista
 #05-01, Singapore 486051
 Tel: (65) 6265 0677 Fax: (65) 6265 4775
 Email: customer.care.sg@akzonobel.com
 Emergency hotline: (65) 6336 7608

Any advice recommendations, information, assistance or service provided by AkzoNobel Paints in relation to goods manufactured or marketed by it or their use or any application is given in good faith. However, advice, recommendations, information, assistance or service provided by AkzoNobel Paints is provided without expressed or implied warranties.