

VIVE ACRYLIC®

Acrylic Paint for Exterior Use



DESCRIPTION

VIVE ACRYLIC is an acrylic paint for exterior use, suitable for the renovation of new and old surfaces such as plaster, concrete and wooden surfaces with very good weather resistance. It represents the economic and reliable solution for the professionals in places where frequent painting and renovation is needed such as schools, hotels, big public works and in surfaces that get tarnished continuously from graffiti, by offering a guaranteed result at an exceptional price. It has very good working properties, dries fast and has great hiding power and strong adhesion.

Ideal for Frequent Painting

Good Resistance to Weather Conditions

PRODUCT INFORMATION

Type: 100% acrylic paint.

Application method: Roller, brush or airless spray.

Thinning: 5-10% clean water.

Spreading rates: About 11 m² per liter per coat on previously prepared surfaces.

Drying times: Touch dry after 1 hour and recoatable after 3 hours.

Drying time depends on weather conditions (humidity, temperature)

Colours: It is available in white. Also, it is available through VIVECHROM's tinting system CHROMOSYNTHESIS in unlimited number of shades.

Storage: Store between 5° C to 40° C.

VOC (Volatile Organic Compounds)

EU limit value for this product category A/c Exterior walls of mineral substrate: 40g/l (2010). This product contains max 14g/l VOC.





VIVE ACRYLIC® Acrylic Paint for Exterior Use

SURFACE PREPARATION

- Surfaces must be clean, dry and free from all defective and poorly adhering materials, dirt, grease and salts.
- Dry sanding, flame cutting and/or welding of the dry paint film will give rise to dust and/or hazardous fumes. Wet sanding/flattening should be used wherever possible. If exposure cannot be avoided by the provision of local exhaust ventilation, suitable respiratory protective equipment should be used.
- For new or coated surfaces with chalking: prime with ASTARI VIVEDUR solvent based primer or VIVE PRIMER 100% ACRYLIC PRIMER FOR EMULSION PAINTS.
- For the refinishing of sound surfaces apply directly two coats of **VIVE ACRYLIC**.

APPLICATION

- Thin with 5-10% clean water and stir well before use.
- Apply two coats of VIVE ACRYLIC for a perfect result.
- Apply the paint and let it dry at temperatures between 10° C to 35° C.

AFTER USE – WASTE MANAGEMENT

Remove as much paint as possible from brushes and rollers before cleaning • Clean brushes and equipment with water and detergent solution after use.

HEALTH, SAFETY & ENVIRONMENTAL INFORMATION

Keep out of reach of children • If medical advice is needed, have product container or label at hand • Do not get in eyes, on skin, or on clothing • Call a POISON CENTER or doctor if you feel unwell • Contains 1,2-benzisothiazol-3(2H)-one and reaction mass of 5-chloro-2-methyl-4-isothiazolin-3-one and 2-methyl-2H-isothiazol-3-one (3:1). May produce an allergic reaction • Do not empty into drains • Dispose of contents and container in accordance with all national regulations • Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

Poison Center: +30210 7793777

Lift with care – gross weight exceeds 10 kg.

**STIR WELL BEFORE USE - PROTECT FROM FROST
DO NOT APPLY AT TEMPERATURES UNDER 10°C.**

